



Kitchen & Bath



DESCRIPTION	special-purpose, matt, water-based, mould-resistant wall paint for use in bathrooms and kitchens
IMPORTANT CHARACTERISTICS	<ul style="list-style-type: none"> • scrubs and wipes clean very easily • mould-resistant • dirt-repellent • resistant to cleaning agents and disinfectants • vapour permeable • excellent coverage • good, durable elasticity
USES	<ul style="list-style-type: none"> • treating walls and ceilings in humid areas such as kitchens and bathrooms • on mineral substrates such as brick, sand-lime bricks, cement-bonded plaster, concrete, plasterboard and stucco

PRODUCT INFORMATION	
Binding Agent	styrene acrylate dispersion
Density	1.44 kg/L
Theoretical Coverage	6–8 m ² /L depending on means of application, surface roughness and porosity
Finish	matt
Shelf Life	<ul style="list-style-type: none"> • approx. 12 months unopened • keep cool, dry and frost-free.

APPLICATION	
Application	brush or roller
Drying at 20 °C	<ul style="list-style-type: none"> • dust dry after approx. 1 hour • recoat after approx. 12 hours • can be washed and scrubbed clean after approx. 28 days
Conditions	> 10 °C and < 75% relative humidity (optimal)
Dilution	water

AVAILABILITY	
Volumes	available in 1 L and 2.5 L containers
Colour	white and all <i>Color Matching System</i> colours
Base	Base 1, 3 and 7

SYSTEMS	
Preparation	<ul style="list-style-type: none"> • remove dirt and/or flaking or powdery paint layers • carefully remove mould and soap using a suitable agent • remove any loose pieces of cement skin from concrete surfaces • prime powdery or highly absorbent (plaster and/or chalk-based) substrates using AQUAFIX or WALL SEALER
Finishing	<ul style="list-style-type: none"> • full coverage with 1 to 2 coats of KITCHEN & BATH