



# Globatex Color



<b>DESCRIPTION</b>	100% solvent-free wall paint in bright colours
<b>PROPERTIES</b>	<ul style="list-style-type: none"> <li>• good coverage</li> <li>• non-drip</li> <li>• brushstroke-free</li> <li>• easy application</li> </ul>
<b>APPLICATION</b>	Suitable for renovation and new construction work, masonry, plasterwork, concrete, aerated autoclaved concrete (AAC) and plasterboard

PRODUCT INFORMATION	
<b>Binder</b>	Vinylcopolymeer dispersion
<b>Specific Gravity</b>	1,40 kg per ltr
<b>Spreading rate</b>	6 – 8 m <sup>2</sup> per litre depending on means of application and surface
<b>Gloss</b>	Matt
<b>Tenability</b>	<ul style="list-style-type: none"> <li>• Approx. 12 months in unopened packing</li> <li>• Keep cool, dry and frost-free</li> </ul>

APPLICATION DETAILS	
<b>Application methods</b>	<ul style="list-style-type: none"> <li>• apply with brush, roller or airless spraying gun</li> <li>• airless spray pressure 100 - 140 bar, spray nozzle 0,019 - 0,021 inch</li> </ul>
<b>Drying time at 20°C</b>	<ul style="list-style-type: none"> <li>• dust dry after approx. 1 hour,</li> <li>• recoat after approx. 12 hours</li> </ul>
<b>Conditions during application</b>	Optimal > 10°C and r.v. < 75%
<b>Thinner</b>	If necessary thinning with water
<b>Cleaning equipment</b>	Clean with water

SUPPLY	
<b>Packing size</b>	2,5 ltr, 5 ltr and 10 ltr
<b>Colour</b>	<ul style="list-style-type: none"> <li>• white</li> <li>• all colours from every colour guide and every colour sample can be delivered immediately with our Global Colour Matching System</li> </ul>
<b>Basis</b>	basis 1, 2, 3, 4, 5 and 7

SYSTEMS	
<b>Pre-treatment</b>	<ul style="list-style-type: none"> <li>• Substrate has to be clean, dry and dust free</li> <li>• Eventually degrease with GLOBACLEAN</li> <li>• Remove parts that are coming off</li> <li>• Eventually treat strong absorbing substrates with WALLSEALER or AQUAFIX</li> </ul>