



# Quarts Medium



<b>DESCRIPTION</b>	Acrylic dispersion-based textured paint
<b>PROPERTIES</b>	<ul style="list-style-type: none"> <li>• fine to coarse texturing</li> <li>• easily textured</li> <li>• good elasticity</li> <li>• vapour-permeable</li> <li>• good coverage</li> <li>• camouflages irregularities</li> </ul>
<b>APPLICATION</b>	Suitable for coating masonry, plasterwork, aerated autoclaved concrete (AAC) and plasterboard

<b>PRODUCT INFORMATION</b>	
<b>Binder</b>	-
<b>Specific Gravity</b>	1,75 kg per ltr
<b>Spreading rate</b>	3 – 6 m <sup>2</sup> per litre depending on means of application and condition of the substrate
<b>Gloss</b>	Matt
<b>Tenability</b>	<ul style="list-style-type: none"> <li>• approx. 12 months in unopened packing</li> <li>• keep cool, dry and frost-free</li> </ul>

<b>APPLICATION DETAILS</b>	
<b>Application methods</b>	Brush and (structure) roller
<b>Drying time at 20°C</b>	Approx. 2 – 4 hours depending on texture thickness
<b>Conditions during application</b>	Optimal > 10°C and r.v. < 75%
<b>Thinner</b>	If necessary dilute with water
<b>Cleaning equipment</b>	Clean with water

<b>SUPPLY</b>	
<b>Packing size</b>	8 kg and 16 kg
<b>Colour</b>	White and light colours from our Global Colour Matching System
<b>Base</b>	-

<b>SYSTEMS</b>	
<b>Pre-treatment</b>	<ul style="list-style-type: none"> <li>• substrate has to be clean and dry, eventually degrease with GLOBACLEAN</li> <li>• pre-treat strong absorbing substrates with WALLSEALER or AQUAFIX</li> <li>• in case of not attaching substrates, remove loose pieces and primer seal with WALLSEALER</li> </ul>
<b>Finishing</b>	Distribute the paint evenly, let it dry a little and then roll the paint once more to get a good effect